

## Mast Specification

Type	Fork Lift Height h <sub>3</sub>		Mast Lowered h <sub>1</sub>		Mast Extended h <sub>4</sub>		Free Lift Height		Capacity	
	in	mm	in	mm	in	mm	in	mm	Load capacity at 24in/600mm	
									lb	kg
Limited Free Lift 2 Stage Mast	98.4	2500	76.4	1940	139.8	3552	3.7	95	3000	1361
	106.3	2700	80.3	2040	147.7	3752	3.7	95	3000	1361
	118.1	3000	86.2	2190	159.5	4052	3.7	95	3000	1361
	129.9	3300	92.1	2340	171.3	4352	3.7	95	3000	1361
	137.8	3500	96.1	2440	179.2	4552	3.7	95	3000	1361
	141.7	3600	98.0	2490	183.1	4652	3.7	95	2950	1338
	145.7	3700	100.0	2540	187.1	4752	3.7	95	2900	1315
	149.6	3800	102.0	2590	191.0	4852	3.7	95	2850	1293
	157.5	4000	109.8	2790	198.9	5052	3.7	95	2750	1247
	169.3	4300	115.7	2940	210.7	5352	3.7	95	2650	1202
Full Free Lift 3 Stage Mast	177.2	4500	119.7	3040	218.6	5552	3.7	95	2550	1157
	137.8	3500	77.8	1975	179.2	4552	36.3	923	3000	1361
	145.7	3700	80.3	2040	187.1	4752	38.9	988	2900	1315
	157.5	4000	84.3	2140	198.9	5052	42.8	1088	2750	1247
	169.3	4300	88.2	2240	210.7	5352	46.8	1188	2650	1202
	177.2	4500	90.2	2290	218.6	5552	48.7	1238	2550	1157
	185.0	4700	94.1	2390	226.5	5752	52.7	1338	2500	1134
	196.9	5000	98.0	2490	238.7	6062	56.6	1438	2400	1089
	204.7	5200	100.0	2540	246.1	6252	58.6	1488	2350	1066
	216.5	5500	103.9	2640	258.0	6552	62.5	1588	2200	998

## Aisle Requirement for Right Angle Stack WRS14

Aisle Requirement for Right Angle Stack <sup>①</sup>		Load Length				
Load Width	36(915)	in(mm)	36(915)	40(1016)	42(1067)	48(1220)
	40(1016)	in(mm)	92.0(2337)	95.1(2416)	96.8(2458)	101.9(2589)
	42(1067)	in(mm)	93.3(2370)	96.3(2447)	97.9(2487)	103.0(2615)
	48(1220)	in(mm)	94.0(2388)	97.0(2463)	98.5(2503)	103.5(2628)
		in(mm)	96.2(2444)	99.0(2514)	100.4(2551)	105.2(2671)

<sup>①</sup>Add a minimum of 1.2in (300mm) for maneuverability.



## A Series Walkie Reach Stacker

with capacities of 3000lbs



**HANGCHA**  
HC FORKLIFT AMERICA CORPORATION

**Company address:**  
10405-A Granite Street  
Charlotte, NC 28273

Toll Free: (888) 652-8395  
Phone: (980) 888-8335  
Fax: (980) 888-8336

america@hcforklift.com  
www.hcforkliftamerica.com



2023 VERSION / COPYRIGHT 2023

HANGCHA GROUP CO., LTD. reserves the right to make any changes without notice concerning colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.

**Making Material Handling Easier**  
SINCE 1956



## Industrial Walkie Stacker Series


The Industrial Walkie Straddle, Reach, and Counterbalance Stacker make up a series of industrial walkie stackers that can handle dock-to-stock and everything in between. Hangcha's Industrial Walkie Stacker product line offers advantageous head-length and a multi-function control handle with Electric Power Steering (EPS). This system, combined with the standard creep speed feature, gives the operator incredible load handling control with excellent maneuverability. The Industrial Walkie Stacker Series excels in the most demanding operational environments to bring your materials handling capabilities to their full potential.



# A Series Walkie Reach Stacker

The Industrial Walkie Reach Stacker from Hangcha is designed for versatility in the Industrial Walkie Stacker Series. It can act both as a counterbalanced stacker and a straddle stacker thanks to the scissor fork extension system. It acts as a counterbalanced stacker when its forks are extended. This allows it to handle non-standard pallets, enclosed pallets, and enclosed shelves easily. The reach stacker also acts as a straddle stacker when its forks are retracted allowing it to operate flexibly in narrow passages. This makes it perfect for warehouses, supermarkets, and workshops.

Easy  
Efficient  
Economical



## High Performance

- / The Electric Power Steering (EPS) system makes maneuvering and load handling extremely easy.
- / The brushless AC travel motor features excellent acceleration, outstanding climbing ability, low heat emission, and is maintenance-free.
- / The latest CURTIS AC control system is highly efficient thanks to its accurate and stable control.
- / The CANBUS structure makes communication between all of the machine's functions faster and more reliable.
- / The truck's regenerative braking prevents it from sliding on a grade.
- / Tiller, switches, plug connectors, meters, and other components are all parts from industry-known suppliers to ensure reliability, performance, and ease of service.
- / The forks and load backrest have a backward and forward tilt function as a part of the standard configuration. This creates a safer experience when loading and unloading goods.

## Maintenance

- / The brushless AC motor reduces operation costs significantly because it is maintenance-free.
- / The integrated battery indicator meter, timer, and fault self-diagnosis are convenient for maintenance.
- / The back cover can be opened fully to reveal all key components and parts. This is extremely convenient for the maintenance of the entire machine.



FREI Multi-Function Tiller  
1: Forks move forward / backward  
2: Lifting / lowering of forks  
3: Forward / backwards tilting of forks



Travel speed is reduced automatically when the forks are lifted past a specified height.



The structure of the rotary load wheel offers better rolling ability and stability.



The forks' tilting function is easy for loading and unloading pallets.

## Reliability

- / The three-support-point, low center of gravity, and the high-strength steel plate structure feature a large residual load-bearing capacity and a long service life.
- / All wires and cables are protected to increase the reliability of the electrical system significantly.
- / The non-contact proximity switch features a long service life and is reliable.
- / The power plug is fastened to the stacker's body. This prevents the plug from being damaged due to impact when the battery is lifted for installation.

## Safety

- / As the truck's steering angle increases, the truck's speed decreases. This is a standard safety feature.
- / The reach stacker features three types of braking functions, release braking, reverse braking, and emergency braking, for safe operation.
- / The anti-sliding function on a grade ensures a safe operational workspace.
- / The emergency reversing button at top of the tiller protects the operator from being injured in case of an emergency during the backward operation of the truck.
- / The soft landing function reduces the mast's lowering speed automatically when the forks are lowered to a height less than 3.9" from the ground. This is designed to protect the goods from hitting the ground too hard.

## Comfort

- / All movements of the fork can be regulated with stepless speed. This provides more accurate and stable handling of goods.
- / The imported tiller's function buttons are designed to allow the operator to comfortably operate the stacker.
- / The standard configuration creep speed driving function allows the truck to move at slow speeds. This increases the stacker's maneuverability and allows it to stack goods even in confined spaces.
- / The stacker's compact body and large rounded corner design make the truck perfect for narrow aisle operation.
- / The optional battery side roll out makes swapping out the battery fast and easy.

## Standard Specification

- / Brushless AC Drive Motor
- / CURTIS AC Drive & Oil Pump Motor Controller
- / Electronic Power Steering System
- / Automatic Deceleration when Turning
- / Proportional Speed Regulation for all Fork Operations
- / Multi-Function Battery Condition Meter
- / High-Performance Load Wheels
- / 42" Fork Length
- / 7.9-33.5" Range for the Adjustable Outer Distance of Forks
- / Forward and Backward Tilt of the Fork, by 3° and 5° Respectively
- / Load Backrest
- / 106.3" Limited Free Lift 2 Stage Mast with Double Lifting Cylinders
- / Soft Landing System
- / Multi-Function Tiller
- / Speed Limited when Fork is at Elevated Location
- / Horn
- / Key Switch
- / Creep Speed Function
- / Emergency Reversing Function
- / 23.2" Forward Extension Distance of Fork

## Options

- / Various Mast Heights (see mast parameter list for details)
- / Various Fork Lengths
- / Sideshifter
- / Battery Side Extraction
- / Freezer
- / Wire Mesh Mast Screen
- / Storage Box



## A Series Walkie Reach Stacker Specification

Distinguishing Marks	1.1	Manufacturer	HANGCHA GROUP CO.,LTD.	
		1.2	HCFA Model	WRS14
	1.3	Manufacturer's Type Designation	CQDB14-AC2-JNA	
	1.4	Drive: electric(battery or mains),diesel,petrol,fuel gas	Battery	
	1.5	Operator Type: hand,pedestrian,standing,seated,order-picker	Walkie	
	1.6	Rated Capacity/Rated Load	Q (lb/kg) 3000/1400	
	1.7	Load Centre Distance	c (in/mm) 24/600	
	1.8	Load Distance, centre of drive axle to fork	x (in/mm) 15/379	
	1.9	Wheelbase	y (in/mm) 57/1451	
Weight	2.1	Service Weight without Battery	lb/kg 4850/2200	
Wheels & Chassis	3.1	Tires: solid rubber,superelectric,pneumatic,polyurethane	PU	
	3.2	Tire Size, front	in/mm $\Phi 9.8 \times 3.9 / \Phi 250 \times 100$	
	3.3	Tire Size, rear	in/mm $\Phi 3.9 \times 2.8 / \Phi 100 \times 70$	
	3.5	Wheels, number front / rear (x = driven wheels)	1 x / 4	
	3.7	Tread, rear	b <sub>11</sub> (in/mm) 46.1/1170	
Basic Dimensions	4.1	Tilt of Mast Forward/Backward	$\alpha/\beta(^{\circ})$ 3/5	
	4.2	Height, mast lowered	h <sub>1</sub> (in/mm) 80.3/2040	
	4.4	Lift	h <sub>3</sub> (in/mm) 106.3/2700	
	4.5	Height, mast extended	h <sub>4</sub> (in/mm) 147.7/3752	
	4.9	Height of Tiller in Drive Position Min./Max.	h <sub>1.4</sub> (in/mm) 29.7/58.1 (755/1475)	
	4.10	Height of Wheel Arms	h <sub>8</sub> (in/mm) 5.1/130	
	4.15	Height, lowered	h <sub>1.3</sub> (in/mm) 1.4/35	
	4.19	Overall Length	l <sub>1</sub> (in/mm) 91.5 <sup>1)</sup> /2323 <sup>1)</sup>	
	4.20	Length to Face of Forks	l <sub>2</sub> (in/mm) 49.3 <sup>2)</sup> /1253 <sup>2)</sup>	
	4.21	Overall Width	b <sub>1</sub> /b <sub>2</sub> (in/mm) 34.3/50 (870/1270)	
	4.22	Fork Dimensions	s/e/l (in/mm) 1.4/3.9/42.1 (35/100/1070)	
	4.24	Fork-Carriage Width	b <sub>3</sub> (in/mm) 36.2/920	
	4.25	Distance between Fork-Arms	b <sub>5</sub> (in/mm) 8.3~33.5 (210~850)	
	4.26	Distance between Wheel Arms	b <sub>4</sub> (in/mm) 42~50 (1070~1270) <sup>2)</sup>	
	4.28	Reach Distance	l <sub>4</sub> (in/mm) 23.2/59	
	4.32	Ground Clearance, centre of wheelbase	m <sub>2</sub> (in/mm) 2.8/70	
	4.35	Turning Radius	W <sub>a</sub> (in/mm) 64.3/1632	
	4.37	Length across Wheel Arms	l <sub>7</sub> (in/mm) 69.96/1777	
			Battery Compartment Width	13.4/340
			Battery Compartment Length	32.2/817
			Battery Floor Height w/ Optional Rollers	in/mm 9.4/240
		Load Backrest Height	h <sub>1.2</sub> (in/mm) 41.3/1050	
		Grade Clearance	D(%) 46.57	
		Top Vertical Braking Arc	Q(^{\circ}) 15	
		Bottom Braking Arc	M(^{\circ}) 10	
		Handle Operating Arc	S(^{\circ}) 65	
Performance Data	5.1	Travel Speed, laden/unladen	mph(kph) 3.4/3.4 (5.5/5.5)	
	5.2	Lift Speed, laden/unladen	ft/min (m/s) 18.66/26.58 (0.095/0.135)	
	5.3	Lowering Speed, laden/unladen	ft/min (m/s) 37.38/29.52 (0.190/0.150)	
	5.8	Max. Gradeability, laden/unladen	% 8/13	
	5.10	Service Brake	Electromagnetic Braking	
Electric Motor	6.1	Drive Motor Rating S2 at 60 min.	hp/kW 4.0/3.0	
	6.2	Lift motor Rating S3 at 15%	hp/kW 4.0/3.0	
	6.4	Battery Voltage/Nominal Capacity K5	V/Ah 24/525	
		Minimum Battery Weight	lb/kg 882/400	
		Maximum Battery Weight	lb/kg 1102/500	
Others	8.1	Type of Drive Control	AC CURTIS	
	10.5	Steering Design	Electric Power Steering	
	10.7	Sound Pressure Level at the Driver's Seat	dB(A) 70	

Note:1), Triplex mast +11mm(0.43in)

2), 2in/50mm increments

Specifications are subject to change without notice.

